

**CHIC4 285/380**



**CHIC5 285/380**



**Our classics!!!**

The CHIC is our mostly sold unit for residential applications.

Wether 4- or 5-stage, the CHIC is the allrounder for at home.

**Specifications:**

- 4 stage reverse osmosis unit
- 380 l/day with 4 bar city pipe pressure (IEM 380 LPD membrane)
- min. required water pressure: 3 bar
- max. water pressure: 8 bar
- automatic shut-off valve (when tank is full)
- 12 liter NSF water tank
- complete installation kit
- installation manual in english
- filter and membrane (285 LPD or 380 LPD)
- faucet
- 25 cm, 5 micron PP sediment filter
- 25 cm, granular activated carbon filter
- inline post carbon filter

**Specifications:**

- 5 stage reverse osmosis unit
- 380 l/day with 4 bar city pipe pressure (IEM 380 LPD membrane)
- min. required water pressure: 3 bar
- max. water pressure: 8 bar
- automatic shut-off valve (when tank is full)
- 12 liter NSF water tank
- complete installation kit.
- installation manual in English
- filter and membrane (285 LPD or 380 LPD)
- faucet
- 25 cm, 5 micron PP sediment filter
- 25 cm, 1 micron PP sediment filter
- 25 cm, granular activated carbon filter
- inline post carbon filter